



RELENTLESS.
DURABLE.
SUREFOOTED AGILITY.
FastCat™ Pro RS



MOW WITH
6 YEAR LIMITED
WARRANTY
CONFIDENCE

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

SUREFOOTED. AGILE. COMMERCIAL MOWING PERFORMANCE

Tough jobs and tight corners have met their match.

Built for the pros who understand the value of their time, the ferocious FastCat™ Pro RS takes speed and maneuverability to a new level. Light on its feet, with a compact frame and low center of gravity, the FastCat™ Pro RS gets around obstacles and clings to steep slopes with confidence and poise. And featuring many of the same operator comfort components of our larger mowers, the FastCat™ Pro RS won't break your back or your bank.

FEATURES:

- » Fully-adjustable, mechanical suspension seat
- » Quick-lift assist foot pedal for easy deck height adjustments
- » Adjustable cutting range from 1.5" to 4.875"
- » Decks built with 7-gauge side skirts and double-layered 10-gauge tops for durability.
- » Wide, flexible molded-polymer discharge chute to resist impact, damage and improve clipping dispersal
- » Commercial Hydro-Gear® transaxles (ZT-3400) provide a transport speed of up to 10 mph
- » DuraDeck™ lifetime deck, deck cradle & engine deck warranty



		FastCat™ Pro RS 942411	FastCat™ Pro RS 942412
ENGINE	Model	Kawasaki® FX850V	Kawasaki® FX850V
	Fuel Capacity	9.5 gal.	9.5 gal.
	Air Filtration	Canister Air Filter	Canister Air Filter
ELECTRICAL	Charging System	15 amp	15 amp
	Clutch	200 ft. lb.	200 ft. lb.
DECK	Mower Deck	DuraDeck™ Cutting System	DuraDeck™ Cutting System
	Leading Edges	Adjustable, 2 positions	Adjustable, 2 positions
	Width	52"	61"
	Anti Scalp Rollers	3	6
	Cutting Height	1.5" – 4.875"	1.5" – 4.875"
	Blade Tip Speed	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
FRAME	Discharge Chute	Flexible Molded Polymer	Flexible Molded Polymer
	Form Welded	Welded 7-gauge steel	Welded 7-gauge steel
	Machine weight	840 lbs.	905 lbs.
TRANSMISSION	Type	Hydro-Gear™ ZT-3400 Hydrostatic Transaxles	
	Displacement	12 cc	12 cc
	Oil Capacity	4 qts.	4 qts.
	Ground Speed	10 mph	10 mph
WHEELS	Drive Wheel Size	23 x 10.5-12	23 x 10.5-12
	Front Caster Size	13 x 6.5-6	13 x 6.5-6
	Caster Type	Pneumatic	Pneumatic
SEAT	Description	High Back w/Armrests	High Back w/Armrests
	Fore-Aft Adjustment	Seat Slide Lever	Seat Slide Lever
WARRANTY		6-year / 2000 hour MOW WITH CONFIDENCE™ Limited Warranty	

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT BOBCATTURF.COM | 866-469-1242

