

# PROCAT™ 6000MX



MODEL NUMBER	9996005	9996006
<b>ENGINE</b>		
Model	Kaw FX850V	Kaw FX850V
Displacement (cc)	852	852
Fuel Capacity (gal)	15	15
Air Filter	Canister Air Filter	
<b>ELECTRICAL</b>		
Charging System (amp)	15	15
Clutch (ft lb)	225	225
<b>DECK</b>		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width (in)	61	61
Adjustable Anti-Scalp Rollers	6	6
Cutting Height (in)	1–5.5	1–5.5
Blade Tip Speed	18500 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
<b>FRAME</b>		
Front & Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	
Machine Length (in)	83	83
Machine Weight—Wet (lb)	1464	1517
<b>TRANSMISSION</b>		
Type	HG ZT-4400 Hydrostatic Transaxles	HG Pumps with HG Wheel Motors
Pump Displacement (cc)	12	12
Oil Capacity (qt)	4.5 each	9
Forward Speed (mph)	0–12	0–11
Reverse Speed (mph)	0–4	0–4
<b>WHEELS</b>		
Drive Wheel Size	24 x 12.0–12, 6-Spoke	24 x 12.0–12, 6-Spoke
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On
<b>SEAT</b>		
Description	High-Back, Full-Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	
<b>WARRANTY</b>	6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty	

**Parts & Accessories:** Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, BOSS-Vac™ Pro 12-bushel, BOSS-Vac™ 8-bushel, No-Flat Caster Wheel Options, 61-inch Wide Track Kit, Magnetic Light Kit—12V, Striping Kit (48", 52", 61"), Light Kit—Footplate, Operator-Controlled Discharge Chute



## FIERCELY INDEPENDENT.

BOBCATTURF.COM