

# QUICKCAT™ 4000



MODEL NUMBER	912360	912480	912520	912610
<b>ENGINE</b>				
Model	Kaw FX600V	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement (cc)	603	726	726	726
Fuel Capacity (gal)	5.1	6.5	6.5	6.5
Air Filter	Dual Element			
<b>ELECTRICAL</b>				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	125	200	200	200
<b>DECK</b>				
Mower Deck	DuraDeck™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	36	48	52	61
Adjustable Anti-Scalp Rollers	3	4	4	7
Cutting Height (in)	1.5–4.5	1.5–4.5	1.5–4.5	1.5–4.5
Blade Tip Speed	17600 fpm @ 3550 Engine rpm	17800 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
<b>FRAME</b>				
Front & Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing			
Machine Length (in)	64	64	64	68
Machine Weight—Wet (lb)	800	961	991	1028
<b>TRANSMISSION</b>				
Type	HG ZT-3100 Hydrostatic Transaxles		HG ZT-3400 Hydrostatic Transaxles	
Pump Displacement (cc)	10	12	12	12
Oil Capacity (qt)	4	4	4	4
Forward Speed (mph)	0–9	0–10.5	0–10.5	0–10.5
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3.5
<b>WHEELS</b>				
Drive Wheel Size	20 x 8.0–10	23 x 8.5–12	23 x 10.5–12	23 x 10.5–12
Front Caster Wheel Size	11 x 4.0–5	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
<b>SEAT</b>				
Adjustment	Flip Up and Latch			
Rider Pad	Tethered, Removable for Service			
Vibration Isolation	Dampened			
<b>WARRANTY</b>	6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty			

**Parts & Accessories:** Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, Hydro Cold-Start Kit (36", 48", 52"), No-Flat Caster Wheel Options, Magnetic Light Kit—12V, Operator-Controlled Discharge Chute



## FIERCELY INDEPENDENT.

BOBCATTURF.COM