



READY
TO TAME THE
TOUGHEST TURF

Introducing the
XRZ™ Pro



DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

PROFESSIONAL PERFORMANCE AND OUTSTANDING VALUE

The new BOB-CAT® XRZ™ Pro is our latest professional grade mower built for the lawn care contractor and the homeowner who wants to mow like one. Based on 60 years of engineering and manufacturing excellence, this latest edition to our zero-turn mower line comes packed with innovative new features. The XRZ™ Pro combines superior value with the toughness and reliability you've come to expect from a BOB-CAT®.

THE ALL-NEW XRZ™ PRO FEATURES:

- » TufDeck™ Pro 10-gauge fabricated, welded and reinforced steel mower deck
- » A choice of 48", 52" or 61" mowing decks
- » Patented Double Wave™ baffle system for maximum vacuum and lift
- » Powerful Kawasaki® FX Series Engines
- » HG ZT-3400 Twin Hydrostatic Transaxles for smooth performance and agility
- » High-back EVC bucket suspension seat with armrests
- » Flip-up floor plate and open frame design
- » Large 22" drive wheels
- » 6-gallon fuel capacity
- » 6-year / 1000 hr MOW WITH CONFIDENCE™ Limited Warranty



		XRZ™ Pro 942620	XRZ™ Pro 942621	XRZ™ Pro 942622
ENGINE	Model	Kawasaki® FX651V	Kawasaki® FX691V	Kawasaki® FX730V
	Fuel Capacity	6 gal.	6 gal.	6 gal.
	Air Filtration	Dual stage canister	Dual stage canister	Dual stage canister
ELECTRICAL	Charging System	15 amp	15 amp	15 amp
	Clutch	125 ft. lb.	125 ft. lb.	125 ft. lb.
DECK	Mower Deck	TufDeck Pro	TufDeck Pro	TufDeck Pro
	Leading Edges	Adjustable front lip standard	Adjustable front lip standard	Adjustable front lip standard
	Width	48"	52"	61"
	Anti Scalp Rollers	3	3	7
	Cutting Height	1.5" - 4.875"	1.5" - 4.875"	1.5" - 4.875"
	Blade Tip Speed	17,365 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Extra Large Discharge Chute	Flexible molded polymer	Flexible molded polymer	Flexible molded polymer
FRAME	Form Welded	Welded 7-gauge steel 1.5 x 2.5" steel tubing 758 lbs.	Welded 7-gauge steel 1.5 x 2.5" steel tubing 774 lbs.	Welded 7-gauge steel 1.5 x 2.5" steel tubing 817 lbs.
	Machine weight			
TRANSMISSION	Type	HG ZT-3400 Twin Hydrostatic Transaxles	HG ZT-3400 Twin Hydrostatic Transaxles	HG ZT-3400 Twin Hydrostatic Transaxles
	Displacement	12 cc	12 cc	12 cc
	Oil Capacity	4 qts.	4 qts.	4 qts.
	Ground Speed	8 mph	8 mph	8 mph
WHEELS	Drive Wheel Size	22 x 11.0-10	22 x 11.0-10	22 x 11.0-10
	Front Caster Size	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic
SEAT	Description	High-back EVC bucket with armrests	High-back EVC bucket with armrests	High-back EVC bucket with armrests
	Fore-Aft Adjustment	Seat slide lever	Seat slide lever	Seat slide lever

WARRANTY

6-year / 1000 hour MOW WITH CONFIDENCE™ Limited Warranty

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT BOBCATTURF.COM | 866-469-1242

