

XV2

FISHER



THE ALL-NEW HEAVY-DUTY XV2™ V-PLOW

Built tougher than winter, the new, heavy-duty 10' 6" FISHER® XV2™ v-plow comes equipped with extreme flared wings—up to 45"—and double-acting cylinders to easily handle anything thrown in its path. Plus, the heavy-duty XV2 is qualified for vehicles up to Class 6, so it's not just hard-working, it's versatile too.

FISHERPLOW.COM

FISHER® XV2™

10' 6" V-Plow



ADVANTAGES

- Purpose built for Class 4-6 trucks
- InstaLock double-acting cylinders
- Trip-Edge design

AVAILABLE ACCESSORIES

- Shoe Kits (standard wear and high wear)
- Rubber Deflectors
- Back Drag Edge Kit*
- Carbide Cutting Edges
- 5/8" Steel Cutting Edges
- Poly Cutting Edges

*Not compatible with shoe kits on v-plows

BLADE DESIGN

- The 10' 6" XV2™ v-plow is constructed with 4 vertical ribs and 8 exclusive x-bracing ribs for structural integrity and torsional strength
- Thicker moldboards and a more robust base angle with additional hinge points distinguish this blade from the other models

NEW HEAVY-DUTY T-FRAME

- A larger center snow control and totally new T-frame uses a solid, one piece construction, from front to back, and includes integrated blade angle stops and oscillating pivot bar

EXTREME FLARED WINGS

- Wings soar from a 35" center height up to 45" at the outer edges to bust through big drifts, carry more snow and windrow wide-open areas

STANDARD FEATURES

- Curb guards
- Blade angle stops
- Choice of new INTENSIFIRE™ LED Headlamps with EdgeView™ Technology or INTENSIFIRE Dual-Halogen Headlamps

MOLDBOARD AVAILABILITY

- Available in powder coated or stainless steel

Blade Width	Plow Type	Moldboard Options	Blade Height (At Center)	Blade Height (At End)	Blade Thickness	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width	Approximate Weight*	Cutting Edge	Wear Shoes	Mount Type
7' 6" (2.29 m)	V-Plow	Stainless	31" (78.74 cm)	37" (93.98 cm)	14 ga (1.98 mm)	4	12	1 1/2" x 10" (4.45 cm x 25.40 cm)	1 3/4" x 11" (4.45 cm x 27.94 cm)	Full Angle: 6' 7" (2.01 m) Scoop: 6' 4" (1.93 m) Full V: 6' 10" (2.08 m)	914 lb (414 kg)	3/8" x 6" (0.95 cm x 15.24 cm) 1/2" x 6" (1.27 cm x 15.24 cm)**	Optional	Minute Mount® 2
8' 6" (2.59 m)	V-Plow	Steel/ Stainless	31" (78.74 cm)	38" (96.52 cm)	14 ga (1.98 mm)	4	12	1 1/2" x 10" (4.45 cm x 25.40 cm)	1 3/4" x 11" (4.45 cm x 27.94 cm)	Full Angle: 7' 5" (2.26 m) Scoop: 7' 2" (2.18 m) Full V: 7' 8" (2.34 m)	957 lb (434 kg)	3/8" x 6" (0.95 cm x 15.24 cm) 1/2" x 6" (1.27 cm x 15.24 cm)**	Optional	Minute Mount 2
9' 6" (2.90 m)	V-Plow	Steel/ Stainless	31" (78.74 cm)	39" (99.06 cm)	14 ga (1.98 mm)	6	12	1 1/2" x 10" (4.45 cm x 25.40 cm)	1 3/4" x 11" (4.45 cm x 27.94 cm)	Full Angle: 8' 6" (2.59 m) Scoop: 8' 2" (2.49 m) Full V: 8' 7" (2.62 m)	1044 lb (473 kg)	1/2" x 6" (1.27 cm x 15.24 cm)	Optional	Minute Mount 2
10' 6" (3.20 m)	V-Plow	Steel/ Stainless	35" (88.90 cm)	45" (114.30 cm)	Steel: 11 ga (3.05 mm) Stainless: 12 ga (2.66 mm)	6	12	1 1/2" x 10" (4.45 cm x 25.40 cm)	2" x 11" (5.08 cm x 27.94 cm)	Full Angle: 9' 9" (2.97 m) Scoop: 9' 7" (2.92 m) Full V: 9' 11" (3.02 m)	1222 lb (554 kg)	1/2" x 6" (1.27 cm x 15.24 cm)	Optional	Minute Mount 2

*Plus vehicle mount
**Optional accessory



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle weight ratings with a snowplow. This product is manufactured under the following patents US: 6,944,978; 7,400,058; 7,430,821; 7,681,334; 7,737,576; 7,797,859; 9,200,418; 9,822,563; CAN patents: 2,356,036; 2,632,102; 2,843,990; other patents pending. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: EdgeView™, FISHER®, INTENSIFIRE™, Minute Mount® 2, STEEL-CASTER™, XV2™.